# A011: SELEXEL

super high solids metallised polish

## **Description of product**

A metallised polish for extreme strength and durability coupled with ease of removability. Non-yellowing cross linked polymer film. Does not discolour even the lightest floor. Produces a deep shine with excellent slip resistance. Responds brilliantly to all spray burnishing techniques.

## **Product Uses**

For all linoleum, P.V.C., rubber, sealed cork, sealed wood, terrazzo and thermoplastic floors. N.B. Not suitable for unsealed wood, unsealed cork or laminate flooring.

#### Directions

Selexel must be applied to a clean grease free floor. Strip old polish with Selstrip or Selate then rinse thoroughly with clean water, allow the floor to dry. Apply a thin even film of Selexel using a clean lint free mop or applicator. Apply a second coat when the first is dry (approximately 30 mins), May be buffed as required to enhance gloss, COVERAGE; 60 square metres per litre, MAINTENANCE; Damp Mopping; As required using Lemon Floor Jell or Selclen. Spray cleaning/burnishing: Regular use of Fast Lane or Selsheen will enhance appearance and life expectancy.

## iNsight Supported

iNsight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit http://www.selden.co.uk/insight

### iNsight recommended product uses

Flooring - applying floor polish (mop application)



## Product Hazards and PPE Requirements



Risk Phrases NC Not classified Safety Phrases

S2 Keep out of the reach of children, P13 Safety data sheet available for professional user on request

### Technical Data

An advanced blend of styrene/acrylic polymer, wax, wetting agents, film-forming agents Composition and preservative in a water based emulsion form incorporating metal cross linking

Appearance Thin, translucent emulsion

Colour White Viscosity <10cps 1.039 Density На 8.6

Activity

Fragrance Characteristic slightly sweet

Stability Two years minimum in unopened container

Storage Protect from freezing

25%





accredited testing laboratory No. 4204



**SELDEN** 

formulating testing manufacturing

> the highest standards

## **Environmental Profile**

### Biodegradability

water

All surfactants contained in Selden • We set ourselves industryleading standards. the EU Detergent Directive 2005 - • If it can be recycled, it will be recycled. 2004/648/EC. This requires all surfactants to break down both quickly and completely into

## Selden Environmental Charter

- Products meet the requirements of Selden minimises wastage, packaging and transportation. 14001 Environmental System
  - Our chemicals policy exceeds regulatory requirements.
  - We don't expect other people to clean up after us.
  - · Conserving energy, preserving resources.
- harmless material such as CO2 and By being innovative, we strive to do better.
  - . We like to work in partnership with our clients. Visit our website for more information.

## **External Accreditations**

9001 - Quality System

DEFRA endorsed Sustainable 18001 - Health & Safety System Cleaning guidance IPPC Certified Manufacturer

Sustainability

Product conforms with the

## COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



## www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages



english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.

### Selden Research Limited

Staden Business Park, Staden Lane, Buxton

Derbyshire, SK17 9RZ

Tel: 01298 26226 | Fax: 01298 26540 | Email: info@selden.co.uk | web: www.selden.co.uk







