



F032 : SELATE

ammonia free metallised polish stripper

Description of product

No choking ammonia fumes. Quick removal of all emulsion and metallised polishes even those 'aged on'. Controlled foam for use with suction driers and combined machines. Modern chelating action "unlocks" metallised polishes.

Product Uses


For the stripping of metallised and non-metallised polish from linoleum, rubber, sealed wood, terrazzo and thermoplastic floors. Effective heavy duty formulation for the removal of impacted dirt from concrete and non-porous surfaces.

Directions

Polish stripping - dilute Selate 1 part to 10 parts hot water. Allow to soak on floor for 10-15 minutes. Scrub thoroughly, preferably with a scrubbing machine fitted with a nylon scrubbing pad. Remove solution with a mop or suction drier. Rinse thoroughly and allow to dry before reapplying polish.

iNsight Supported


iNsight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit <http://www.selden.co.uk/insight>



iNsight recommended product uses

	typical dilution
Flooring - floor stripping / polish removal (machine)	1 : 10
Flooring - floor stripping / polish removal (mop)	1 : 10

Product Hazards and PPE Requirements

CORROSIVE

Risk Phrases
R34 Causes burns.

Safety Phrases
S1/2 Keep locked up and out of the reach of children., S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice., S28 After contact with skin, wash immediately with plenty of water., S36/37/39 Wear suitable protective clothing, gloves and eye/face protection., S45 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).

Technical Data

Composition A fast acting formulation containing alkali builders, surfactants, penetrating agents, and sequestrants.

Appearance Clear liquid

Colour Blue

Cloud Point 38

Density 1.068

pH >13.5

Stability 2 years in a unopened container

Environmental Profile

Biodegradability

All surfactants contained in Selden Products meet the requirements of the EU Detergent Directive 2005 – 2004/648/EC. This requires all surfactants to break down both quickly and completely into harmless material such as CO2 and water.

Selden Environmental Charter

- We set ourselves industry leading standards.
- Selden minimises wastage, packaging and transportation.
- If it can be recycled, it will be recycled.
- Our chemicals policy exceeds regulatory requirements.
- We don't expect other people to clean up after us.
- Conserving energy, preserving resources.
- By being innovative, we strive to do better.
- We like to work in partnership with our clients.


Visit our website for more information.

External Accreditations

9001 - Quality System
14001 - Environmental System
18001 - Health & Safety System
IPPC Certified Manufacturer


Sustainability

Product conforms with the DEFRA endorsed Sustainable Cleaning guidance



COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages

english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.





UKAS
accredited testing
laboratory No. 4204



SELDEN
formulating
testing
manufacturing
to
the highest
standards

Selden Research Limited

Staden Business Park, Staden Lane, Buxton
Derbyshire. SK17 9RZ

Tel : 01298 26226 | Fax : 01298 26540 | Email : info@selden.co.uk | web : www.selden.co.uk

